



EN ISO 20345:2022/A1:2024



GREENBALL

MABLOO BOA®
60540-02L
S3S FO HI *CI HRO SR
Size: 38-48

Weight: 620 gr.

Fit: 11

Working Environment:

Multipurpose, Finishing-off building, Components and Automotive, ESD Areas



FEATURES

UPPER

MicroFiber Rubber 1,8-2,0 mm

LINING

3D Green Air 320 gr.

ANTISLIP LINING

DUALMICRO

INSOLE

QRS02 Green

TOE CAP

Nano Toe SXT

RESISTANCE TO PERFORATION

KK7 Antiperforation recycled PS

TYPE

Low Shoe

SOLE

PU-D30-VIBRAM® RECYCLED ECOSTEP

Ecostep PRO by Vibram with high performance and durability, contributes to a lower environmental impact. Midsole D30 DECELL with TPU "PODSKIN" film. Midsole PU medium density BASF with Cycled® recycled material. Standard Antislip SR.

Boa® lace length

L6- 85 cm

TECHNOLOGIES

Removable Insole



Anatomical breathable insole. Resistant fabric with recycled open-cell foam that absorbs shocks and reduces fatigue. Eliminates sweat with its high ability to evaporate it. Continuous comfort for months and months of use



Protection elements



Composite toe cap, reinforced with carbon nanotubes. Resistant > 200J Non metal perforation resistant insert to over 1100 N with a 3.0 mm truncated cone nail. Protection over the entire sole of the foot. Flexible and comfortable.



Lateral stability

dynamic HC control
technology

Ergonomic rigid internal structure. It houses the heel into the right seat, adjusting the foot support and control of the ankle sideways movements. It keeps the foot tight to the shoe, allowing the perfect fit.



Torsional stability

STABIL•ACTIVE

Support made of rigid plastic material. It supports the heel bone, the instep and tarsal joints, without altering energy absorption. A support for the natural movement of the foot; it provides comfort and greater stability.



Electrical features




ESD footwear discharge static electricity and avoid damaging surrounding objects; they are designed in compliance with the following standards: IEC EN 61340-5-1:2016 - IEC EN 61340-4-3:2018 - IEC EN 61340-4-5:2018.

Other

GREENBALL

Greenball is the result of extensive ergonomic studies, a perfect combination of green materials and technologies that ensure "Highly Controlled Stability" and a feeling of well-being from the feet to the spine.



PU - RUBBER

SOLE 60

SLIP RESISTANCE

EN ISO 20345:2022

BASIC CERAMIC WITH NALS

FORWARD HEEL SLIP	≥ 0.31	0,58
BACKWARD FOREPART SLIP	≥ 0.36	0,60

SR CERAMIC WITH GLYCERINE

FORWARD HEEL SLIP	≥ 0.19	0,26
BACKWARD FOREPART SLIP	≥ 0.22	0,30